# Accent™ Ridging







Turn generic into standout and sharpen up your roofline with Accent™ Ridging, a low-line ridge system to enhance terracotta tiles.

Whether flat or shaped in tile profile, Accent™ Ridging aligns ridge capping end-to-end in one smooth line without steps.

For the ultimate contemporary silhouette of clean lines and sleek simplicity, with all the benefits of terracotta.









## Why Terracotta?

### **Premium Quality:**

Crafted from select natural clays that are kiln-fired to temperatures of 1100°C for exceptional character and strength that is virtually maintenance-free.

### **Stunning Colour:**

In the latest new hues, a vitreous ceramic coating protects from harsh UV exposure for superior colour performance and smooth surface finish.

### **Design Freedom:**

Boral's Terracotta Shingle™ tiles can achieve a roof pitch as low as 15 degrees. Team with low-line Accent™ Ridging to remove bulkiness across ridgelines and achieve a clean sleek finish.

### **Exceptional Performance:**

Salt-safe and frost resistant, terracotta Accent™ Ridging is suitable for all locations including coastal areas. Just ask us for a copy of our 50-year guarantee.



Terracotta Shingle™



French



Swiss

# Accent<sup>™</sup> Ridging

# accentuate clean, contemporary lines

- Suitable for all Boral Terracotta tile profiles
- No more bulky ridgelines to achieve an integrated look across your home
- Low ridge profile may assist where height restrictions apply
- CSIRO tested to ensure superior weatherproofing
- No metal flashings needed under hip and top ridge

## Accent<sup>™</sup> Ridge specifications

### Accent™ Ridge Cap

Actual Length Actual Width	430mm 265mm
Exposed Length	415mm
Exposed Width	265mm
No. of pieces per lineal metre	2.5



435mm
265mm
415mm
265mm



### Finished Height above Roof Frame ridge line

Profile	Standard Ridge Profile Height	Accent™ Ridge Profile Height
Shingle	130mm	110mm
French	135mm	115mm
Swiss	155mm	135mm

Note: Above heights are calculated on a roof pitch of 25 degrees with 38mm thick tile battens.




Figure 1: Accent<sup>™</sup> Ridge Fixing for N4

## Security Fixing

- Flexible pointing is acceptable for N1,N2 & N3 wind classifications.
- Additional mechanical fixing is required for N4 and greater wind classifications. See Figure 1.







Top Ridge Shingle Roof



Top Ridge French Roof



Hip Roof



Apex Finish

#### IMPORTANT INFORMATION

Terracotta tile products and Accent™ Ridges are individually kiln-fired and feature minimal natural variations that mean they are not uniformly flat. Each tile and Accent™ Ridge can vary up to 5mm-8mm along the horizontal plane and pallets should be blended across the roof to achieve a beautiful result of authentic character. Some photos featured in this flyer are artists impressions of how Terracotta roof tiles will look on a roof. These images are computer generated. Please ensure a tile display is viewed prior to making a final product decision. Product information contained in this leaflet is correct at the time of printing however is subject to change without notice. Colours shown are indicative only and should not be used for final selection. Colours are subject to change without notice. Check print date prior to product selection. Roof tile colours may vary in shades throughout the manufacturing process therefore it is important that roof tiles are blended consistently across the roof. Boral Roofing will replace any roof tile which fails the Australian Standard 2049 roof tiles. Please ask for a copy of the Boral Roofing 50 year guarantee before making your purchase. During transportation and installation small blemishes such as scuffing and chip marks may occur. These are not considered a production fault and will not detract from the performance of the roof tile. © copyright Boral Montoro Pty Limited. ™ Accent is a trademark of Boral Montoro Pty Limited. Print date February 2009.